

Resene product labels are updated from time to time. This label is provided as a guide for this product and may differ from the label on the container you purchase.

Please discuss your project with your local Resene ColorShop team or reseller to ensure you have the right products to give you the best quality finish for your specific project.

net contents 1 litre

LL73701 11/23

KEEP OUT OF REACH OF CHILDREN

# Resene

## Brushable Crack Filler

exterior/interior

### SAFETY PRECAUTIONS

Read label before use. Keep out of reach of children. This material is quite bland; with vapour, occasional skin contact and even minor ingestion having negligible hazard. Repeated skin contact may, and any eye contact will, cause irritation. Harmful to aquatic life with long lasting effects.

### PRECAUTIONS

DO NOT BREATHE DUST, MISTS, VAPOURS OR SPRAYS. DO NOT EAT, DRINK OR SMOKE WHEN USING THIS PRODUCT.

Store in original or correctly labelled container, tightly closed, in a well-ventilated area indoors, away from foodstuffs, at an ambient temperature and avoid freezing conditions. Avoid release to the environment.

### FIRST AID

IF SWALLOWED: Call a POISON CENTRE, doctor or first aider if you feel unwell.

IF ON SKIN (or hair): Wash with plenty of soap and water. If skin irritation occurs get medical advice or attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so. Continue rinsing. If eye irritation persists get medical advice or attention.

When seeking medical advice take this container with you.

Further information can be obtained from

AUST: POISONS INFORMATION CENTRE 131 126 or call Resene 1800 738 383.

NZ: NATIONAL POISONS CENTRE 0800 POISON (764 766) or call Resene 0800 737 363.

For use as a filler.

For full technical instructions see Data Sheet D811.

**SPILLS:** Wear appropriate protective clothing. Absorb with sand or earth. Collect and seal in properly labelled drums. Do not allow to enter drains or to run off into waterways. Refer to local waste management authority.



9 4 1 8 0 2 2 0 2 7 7 8 2

DO NOT TINT

Resene Brushable Crack Filler is a convenient way to deal with small cracks in concrete buildings, which may still be cyclically moving up to 25%. It is designed to handle cracks up to a maximum of 2mm wide.

### Preparation

- Cracks must be clean before application, which includes treating the moss and mould that they often harbour. Such treatment may be part of the moss and mould/waterblasting specification for the whole contract or individual to the cracks to be treated. In the latter case, wire brushing is recommended to remove dirt and loose material.

- If there is evidence of efflorescence, clean, then treat with Resene Aquapel (see Data Sheet D65) to reduce the incidence of further problems.

### Priming

- Prime surfaces which are in poor condition, friable, powdery or chalky or affected by efflorescence with Resene Sureseal (see Data Sheet D42).

- If the edges of the crack are weak and crumbly, wire brush the crack edges to remove loose material, then prime with a penetrating sealer, such as Resene Sureseal.

- Sound cementitious substrates, including fibre cement, do

not usually need priming. Prime smooth/glossy cementitious surfaces with Resene Concrete Primer (see Data Sheet D405) to assist with topcoat adhesion. Spot prime nail heads (not galvanised) with Resene ArmourX Rust-Arrest (see Data Sheet RA30A). For galvanised nail heads use Resene ArmourX GP Metal Primer (see Data Sheet D411).

### Application

- Apply multiple coats brushing across the grain until the crack is filled. Do not brush down the crack.

- Maintain good ventilation throughout the drying and post application curing period to ensure the paint is properly cured. This may require use of an extraction system when painting in marginal painting conditions. Do not use gas or diesel burners to heat coated area as these produce water that will inhibit drying and curing. Poor ventilation may affect appearance and performance.

- Resene Brushable Crack Filler is suitable for cracks up to 2mm. For larger cracks please ask Resene ColorShop or reseller staff for assistance.

### Overcoating

As Resene Brushable Crack Filler will not leave a perfectly smooth surface it is recommended for use under textured or high build coatings.

### Maintenance

(after a minimum of four weeks' drying)

See the Resene Caring for your paint finish brochure or the Resene website for full cleaning instructions.

### Be PaintWise

For tips on responsible disposal of paint, cleaning equipment and minimising the impact of your decorating on the environment see the Resene website. Do not discharge any paint into the environment. Resene PaintWise (NZ) or paintback.com.au (Australia) accepts residual unwanted paint and packaging. Or contact your Local Authority for disposal information. Please recycle.



Resene  
the paint the professionals use



In Australia: Resene Paints (Aust) Limited  
7 Production Ave, PO Box 918, Ashmore City, QLD 4214  
Ph 1800 738 383 Visit [resene.com.au](http://resene.com.au)

In New Zealand: Resene Paints Limited  
Vogel St, PO Box 38242, Wgtn Mail Centre, Lower Hutt 5045  
Ph (04) 577 0500 Visit [resene.co.nz](http://resene.co.nz)

### Quick check

**Use on:** Exterior and interior cementitious surfaces.

**Coverage:** Dependent on size of crack.

**Dry time:** Typically 1 hour. Drying is slowed by low temperatures and high humidity. Do not apply at temperatures below 10°C or when temperatures are liable to drop below this during the drying period. Do not apply under damp conditions.

**Recoat time:** 3 hours.

**Primer required:** Dependent on surface.

**Usual number of coats:** Multiple until crack filled. Product will dry back and may require recoating to fill the crack.

**Application method:** Brush. Do not roll or spray as the product needs to be worked across the crack.

**Clean up:** Water. DO NOT THIN.

**Colour:** Light grey

**Before use:** Stir well with a wide flat stirrer.

Enjoy the Resene Promise of quality on premium paints. See your Resene ColorShop or the Resene website for a copy.

In every case it is recommended that the appropriate Data Sheet and Safety Data Sheet are consulted prior to application.

Please ensure that use of this product is compatible with the substrate and surface preparation method and that the colour in this container is the same as selected. Resene does not accept any responsibility for the application of incorrect product to substrate or the application of incorrect colours. Resene products are designed to be used as a system for optimal results. Substitution may cause substandard results or system failure. For further painting advice and information, call 1800 738 383 (AUST), 0800 737 363 (NZ) or visit the Resene website.