

Resene product labels are updated from time to time. This label is provided as a guide for this product and may differ from the label on the container you purchase.
Please discuss your project with your local Resene ColorShop team or reseller to ensure you have the right products to give you the best quality finish for your specific project.

WARNING

Read label before use. Keep out of reach of children. Harmful if swallowed. Causes skin irritation. Causes eye irritation. May cause an allergic skin reaction.

PRECAUTIONS

DO NOT BREATHE FUMES/MISTS/SPRAYS/VAPOURS. USE WITH ADEQUATE VENTILATION. DO NOT EAT, DRINK OR SMOKE WHILE USING. Do not handle until all safety precautions have been read and understood. Store in original or correctly labelled container, tightly closed, in a well-ventilated area indoors, away from foodstuffs, either between 15°C-20°C or at a cool, constant temperature. Store locked up. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear protective gloves and eye/face protection and any other personal protective equipment as required. Wash thoroughly after handling. Do not allow contaminated work clothing out of the workplace. Wash before re-use. Dispose of empty container safely. Consult Resene checklist on environmentally acceptable methods for cleaning equipment and disposing of unwanted paint. Avoid release to the environment.

FIRST AID

IF SWALLOWED: If ingested give water to dilute. Do not cause vomiting. Get medical attention without delay.

IF ON SKIN (or hair): Remove/take off all contaminated clothing and wash before re-use. Wash skin with plenty of soap and water/shower. If skin irritation or rash occurs get medical advice/attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing.

INHALATION: Remove to fresh air. IF BREATHING DIFFICULT GET MEDICAL ATTENTION IMMEDIATELY. Call a POISON CENTRE or doctor/physician if you feel unwell.

When seeking medical advice take this container with you.

Further information can be obtained from
AUST: POISONS INFORMATION CENTRE 131 126
or call Resene 1800 738 383.

NZ: NATIONAL POISONS CENTRE 0800 POISON (764 766)
or call Resene 0800 737 363.

CONTAINS: Liquid hydrocarbons 330-365 gms/L,
Methylated spirits 78-85 gms/L.

For use as a decorative/protective coating.

For full technical instructions see Data Sheet D507.

SPILLS: Use appropriate protective clothing. Absorb with sand or earth. Collect and seal in properly labelled drums. Do not allow to enter drains or to run off into waterways. Refer to local waste management authority.

CLEANING PAINT EQUIPMENT: Brush/roll out as much paint as possible on to newspaper before washing out brushes/rollers with Resene Brush Cleaner or mineral turps. Do not allow mineral turps to enter any drains. Refer to your local Council for disposal of dirty mineral turps.

FIRE: Use foam, carbon dioxide or dry chemical powder.

WARNING

KEEP OUT OF REACH OF CHILDREN

Resene

Danska Teak Oil

natural wood finish

interior



CLEAR

Resene Danska Teak Oil is a highly 'refined' Linseed Oil product designed to bring out the grain of heart timbers such as Rimu and Teak and produces the most natural results when left uncoated.

Preparation

- Ensure surfaces are in sound condition, thoroughly sanded, dry and free from dirt, dust and loose material.
- If mould is present, treat with Resene Moss & Mould Killer (see Data Sheet D80).
- Thoroughly sand bare timber surfaces prior to coating. Finish off with fine sandpaper remembering always to sand with the grain.
- **All sanding dusts may be harmful and appropriate protection must be worn. In particular dusts from old lead or chromate based paints or old building materials containing asbestos may be injurious to health if inhaled or ingested. Seek expert advice if the presence of these materials is suspected.**

• This product may be used on a wide variety of surfaces. If the surface you propose to coat is unsound or not referred to, try a small test area first or contact your local Resene ColorShop or Reseller for advice.

Application

- Apply liberally by brush or rag and allow to penetrate into the surface.
- Avoid skin contact and wear gloves when applying by rag or when wiping off any surplus.
- Wipe excess Resene Danska Teak Oil off with a dry, absorbent lint free cloth, rubbing along the grain. Surplus Danska Oil MUST be wiped off to ensure best results.
- Maintain good ventilation throughout the drying and post application curing period to ensure the paint is properly cured. This may require use of an extraction system when painting in marginal painting conditions. Do not use gas or diesel burners to heat coated area as these produce water that will inhibit drying and curing. Poor ventilation may affect appearance and performance.

Overcoating

- Resene Danska Teak Oil can be left natural or can be overcoated with solventborne Resene Kristal polyurethanes.
- Ensure Resene Danska Teak Oil is thoroughly dry before overcoating with solventborne Resene Kristal polyurethanes.

Precautions

Dispose of impregnated rags very carefully as discarded rags can generate heat and catch fire. Thoroughly rinse rags with detergent and water before discarding.

Be PaintWise

For tips on minimising the impact of your decorating on the environment see the Resene website.



UN NO. 1263 – PAINT

FLAMMABLE LIQUID AND VAPOUR

Keep away from heat/sparks/open flames/
hot surfaces. No smoking.
Keep closed when not in use.

Danska Teak Oil
SDSDanska Teak Oil
TDS**Resene**

the paint the professionals use

In Australia: Resene Paints (Aust) Limited
7 Production Ave, PO Box 924, Beenleigh, Qld, 4207
Phone 1800 738 383 Fax 1800 064 960
Email advice@resene.com.au or visit www.resene.com.au

In New Zealand: Resene Paints Limited
Vogel Street, PO Box 38242, Wellington Mail Centre, Lower Hutt 5045
Phone (04) 577 0500 Fax (04) 577 0600
Email advice@resene.co.nz or visit www.resene.co.nz

Manufactured under a quality system certified as complying with ISO9001 by Telarc SA, an accredited certification body. Printed on environmentally responsible paper, which complies with the requirements of environmental management systems EMAS and ISO14001, using vegetable-based inks.

Quick check

Use on: Interior timber surfaces. Not recommended for floors that are to be polyurethaned.

Gloss level: Low sheen.

Coverage: Up to 30 square metres per litre per coat.

Dry time (minimum): 24 hours depending upon surface type. Drying is slowed by low temperatures and high humidity and is dependent on timber type and varnish.

Recoat time (minimum): 48 hours.

Primer Required: No.

Usual number of coats: One.

Application method: Brush or clean lint-free cloth.

Thinning: Do not thin.

Clean up: Mineral turps.

Thoroughly rinse rags with detergent and water before discarding.

Dispose of impregnated rags very carefully as discarded rags can generate heat and catch fire.

Before use: Stir well with a wide flat stirrer.

Enjoy the Resene Promise of quality on premium paints. See your Resene ColorShop or the Resene website for a copy.

In every case it is recommended that the appropriate Data Sheet and Safety Data Sheet are consulted prior to application.

Please ensure that use of this product is compatible with the substrate and surface preparation method. Resene does not accept any responsibility for the application of incorrect product to substrate or the application of incorrect colours. For further painting advice and information, call 1800 738 383 (AUST), 0800 737 363 (NZ) or visit the Resene website.