

Resene product labels are updated from time to time. This label is provided as a guide for this product and may differ from the label on the container you purchase.
Please discuss your project with your local Resene ColorShop team or reseller to ensure you have the right products to give you the best quality finish for your specific project.

net contents 1 litre

LL22801 6/17

DANGER

KEEP OUT OF REACH OF CHILDREN

Resene

Kwila Timber Stain

exterior



SAFETY PRECAUTIONS

Read label before use. Keep out of reach of children. Causes mild skin irritation. May be harmful in contact with the skin. May cause an allergic skin reaction. Causes serious eye irritation. Harmful if swallowed. Harmful if inhaled. Suspected of causing cancer. May damage fertility or the unborn child. Toxic to aquatic life with long lasting effects. Harmful to terrestrial vertebrates.

PRECAUTIONS

DO NOT BREATHE DUST, FUMES, GAS, MISTS, VAPOURS, SPRAYS. DO NOT EAT, DRINK OR SMOKE WHEN USING THIS PRODUCT.

Store in original or correctly labelled container, tightly closed, in a well ventilated area indoors, away from foodstuffs, either between 15°C-20°C or at a cool, constant temperature. Store locked up. Use in a well ventilated area. Wear protective gloves and clothing, eye and face protection. Use personal protective equipment as required. Ground or bond container and receiving equipment. Avoid release to the environment. Dispose of empty container safely. Consult Resene checklist on environmentally acceptable methods for cleaning equipment and disposing of unwanted paint. Collect spillage.

FIRST AID

IF SWALLOWED: Call a POISON CENTRE, doctor, physician or first aider if you feel unwell.

IF ON SKIN (or hair): Wash with plenty of soap and water. If skin irritation or rash occurs get medical advice or attention. Wash contaminated clothing before reuse.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so. Continue rinsing. If eye irritation persists get medical advice or attention.

IF INHALED: If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. Get medical advice or attention. If exposed or concerned: Get medical advice or attention.

If medical advice is required have product container or label at hand. Further information can be obtained from

AUST: POISONS INFORMATION CENTRE 131 126 or call Resene 1800 738 383.

NZ: NATIONAL POISONS CENTRE 0800 POISON (764 766) or call Resene 0800 737 363.

CONTAINS: Ethylbenzene 90-290 gms/L, Xylene 90-290 gms/L, 1,2,4-Trimethyl Benzene 90-290 gms/L, Dibutyl Phthalate 5-50 gms/L, 3-Iodo-2-Propynyl Butyl Carbamate 0-5 gms/L, Benzotriazol derivatives 0-5 gms/L.

For use as a decorative/protective coating.

For full technical instructions see Data Sheet D501.

SPILLS: Use appropriate protective clothing. Absorb with sand or earth. Collect and seal in properly labelled drums. Do not allow to enter drains or to run off into waterways. Refer to local waste management authority.

CLEANING PAINT EQUIPMENT: Brush/roll out as much paint as possible on to newspaper before washing out brushes/rollers with Resene Brush Cleaner or mineral turps. Do not allow mineral turps to enter any drains. Refer to your local Council for disposal of dirty mineral turps.

FIRE: Use foam, CO₂ dry chemical for extinction.

Resene Kwila Timber Stain is designed for direct application to new and weathered timber decks and furniture to enhance and restore the timber colour and provide protection against water, fungi and U.V. light. As a penetrating material, Resene Kwila Timber Stain will regenerate wood fibres exposed by U.V. light or weather attack and re-build them into a wood-like material.

Preparation

• Ensure substrates to be coated are in sound condition, dry, free from dirt, dust, loose material, oil (including mineral oil based wood finishes or similar) and salt.

• Remove accumulated windblown salt by washing with Resene Paint Prep and Housewash (see Data Sheet D812).

• If mould is present, treat with Resene Moss & Mould Killer (see Data Sheet D80).

• For repaints of existing penetrating stains remove any gross contamination and loose cellulose fibres.

• **All sanding dusts may be harmful and appropriate protection must be worn. In particular dusts from old lead or chromate based paints or old building materials containing asbestos may be injurious to health if inhaled or ingested. Seek expert advice if the presence of these materials is suspected.**

• Always trial Resene Kwila Timber Stain on a representative piece of timber first to ensure it gives the result you want on the actual timber you are coating.

• This product may be used to stain a wide variety of timber surfaces. If the surface you propose to stain is not referred to, try a small test area first or contact your local Resene ColorShop or Reseller for advice.

Application

• Resene Kwila Timber Stain is recommended on Kwila, Cedar, exterior timber, and for restoration of badly weathered timber surfaces. New timber should be treated with Resene Kwila Timber Stain before assembly. Pay special attention to the underside of decks, as they will be difficult to coat after the deck has been assembled. All faces of the timber should be treated with special attention to end grains.

• Before use and regularly during use, stir well with a wide flat stirrer.

• Saturate the surface with Resene Kwila Timber Stain. The worst weathered surfaces will require a second application.

• Resene Kwila Timber Stain will not penetrate existing coatings or very hard latewood bands. Wipe excess Resene Kwila Timber Stain off with a dry, absorbent, lint free cloth rubbing along the grain.

• If applying two coats, apply the second coat after 24 hours and preferably before one week. Protection begins after the full system has been applied.

• Maintain good ventilation throughout the drying and curing period to ensure the paint is properly cured. Poor ventilation may inhibit curing and performance.

• Will typically require maintenance after two summers. Performance is related to the depth of colour applied. Light applications and dressed surfaces may require maintenance sooner, while heavier applications and rough sawn surfaces will require less maintenance.

• Will typically require maintenance after two summers. Performance is related to the depth of colour applied. Light applications and dressed surfaces may require maintenance sooner, while heavier applications and rough sawn surfaces will require less maintenance.

Precautions

• Contains powerful fungicides. Avoid skin contact and wear gloves when wiping off any excess.

• Resene Kwila Timber Stain will be less effective if container is contaminated with water.

• Trafficable areas coated with this unmodified product will not comply with the Building Act Clause D1.3.3(d).

Be PaintWise

For tips on minimising the impact of your decorating on the environment see the Resene website.



UN NO. 1263 - PAINT

FLAMMABLE LIQUID AND VAPOUR

Keep away from heat, sparks, open flames and hot surfaces. No smoking.



Kwila Timber Stain SDS



Kwila Timber Stain TDS

Resene

the paint the professionals use

In Australia: Resene Paints (Aust) Limited
7 Production Ave, PO Box 924, Beenleigh, Qld 4207
Phone 1800 738 383 Fax 1800 064 960
Email advice@resene.com.au or visit www.resene.com.au

In New Zealand: Resene Paints Limited
Vogel Street, PO Box 38242, Wellington Mail Centre, Lower Hutt 5045
Phone (04) 577 0500 Fax (04) 577 0600
Email advice@resene.co.nz or visit www.resene.co.nz

Manufactured under a quality system certified as complying with ISO9001 by TelarcSAI, an accredited certification body. Printed on environmentally responsible paper, which complies with the requirements of environmental management systems EMAS and ISO14001, using vegetable inks.

Quick check

Use on: Exterior timber decks and furniture.

Gloss level: None. Fully penetrating.

Coverage: 3-12 square metres per litre per coat depending on the condition and porosity of the surface.

Dry time (minimum): 24 hours. Drying is slowed by low temperatures and high humidity. Do not apply under damp conditions.

Recoat time (minimum): 24 hours.

Usual number of coats: Two.

Application method: Brush, spray or roller.

Thinning and clean up: Do not thin. Clean up with mineral turps.

Before use: Stir well with a wide flat stirrer.

Enjoy the Resene Promise of quality on premium paints. See your Resene ColorShop or the Resene website for a copy.

In every case it is recommended that the appropriate Data Sheet and Safety Data Sheet are consulted prior to application.

Please ensure that use of this product is compatible with the substrate and surface preparation method and that the colour in this container is the same as selected. Resene does not accept any responsibility for the application of incorrect product to substrate or the application of incorrect colours. Resene products are designed to be used as a system for optimal results. Substitution may cause substandard results or system failure. For further painting advice and information, call 1800 738 383 (AUST), 0800 737 363 (NZ) or visit the Resene website.

