

Resene product labels are updated from time to time. This label is provided as a guide for this product and may differ from the label on the container you purchase. Please discuss your project with your local Resene ColorShop team or reseller to ensure you have the right products to give you the best quality finish for your specific project.

Resene

ProSelect

professional timber flooring finish
blending system

Gloss Base
waterborne interior



WARNING

KEEP OUT OF REACH OF CHILDREN



LL2751020F 8/18

net contents
20 litres

LL2751020B 8/18

SAFETY PRECAUTIONS

Read label before use. Keep out of reach of children. This material is quite bland; with vapour, occasional skin contact and even minor ingestion having negligible hazard. Repeated skin contact may, and any eye contact will, cause irritation.

PRECAUTIONS

USE WITH ADEQUATE VENTILATION. DO NOT EAT, DRINK OR SMOKE WHILE USING.

Store in original or correctly labelled container, tightly closed, in a well ventilated area indoors, away from foodstuffs, either between 15°C-20°C or at a cool, constant temperature. Dispose of empty container safely. Consult Resene checklist on environmentally acceptable methods of cleaning equipment and disposing of unwanted paint. Do not contaminate any water supply. Avoid release to the environment.

FIRST AID

IF INHALED: If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing.

IF SWALLOWED: Rinse mouth. Call a POISON CENTRE, doctor or physician if you feel unwell.

IF ON SKIN (or hair): Wash with plenty of soap and water. If skin irritation or rash occurs get medical advice or attention.

IF IN EYES: Rinse cautiously with water for several minutes. Continue rinsing. If eye irritation persists get medical advice or attention.

If medical advice is required have product container or label at hand.

Further information can be obtained from
AUST: POISONS INFORMATION CENTRE 131 126
or call Resene 1800 738 383.

NZ: NATIONAL POISONS CENTRE 0800 POISON
(764 766) or call Resene 0800 737 363.
For use by professional flooring contractors.

SPILLS: Wear appropriate protective clothing. Absorb with sand or earth. Collect and seal in properly labelled drums. Do not allow to enter drains or to run off into waterways. Refer to local waste management authority.

CLEANING APPLICATION EQUIPMENT:

Brush/roll out as much product as possible onto newspaper before washing brushes and rollers. Dispose of wash-up water onto grassy/unsealed area or into inside sink/basin, NOT into outside stormwater drain where it may harm fish in local waterways.

Please ensure that use of this product is compatible with the substrate and surface preparation method and that the colour in this container is the same as selected.

When using multiple packs of this product on the same project please mix them together before use. Resene does not accept any responsibility for the application of incorrect product to substrate or the application of incorrect colours. Resene products are designed to be used as a standard for optimal results. Substitution may cause substandard results or system failure. For further painting advice and information, call 1800 738 383 (AUST), 0800 737 363 (NZ) or visit the Resene website.

Developed specifically for professional flooring contractors, Resene ProSelect bases are tough low VOC waterborne polyurethanes for use in the Resene ProSelect Blending System designed to enhance and protect hardwood timber floors.

FOR PROFESSIONAL USE ONLY

Important note: All processes for hardwood timber floor coating from the initial consultation with the client, through to final application/finishing and maintenance should follow the guidelines set out in the Australasian Timber Flooring Association (ATFA) Information Guide Manual and Web Site, www.atfa.com.au.

Select desired finish and then mix appropriate components and additives according to the Resene ProSelect Mixing Chart.

Pour sufficient material to cover the immediate area and spread/roll with a smooth continuous motion avoiding excessive pooling of product and pressure on the application equipment. Always maintain a wet edge and ensure correct spread rate is achieved. DO NOT SPREAD TOO THIN. To aid in drying ensure good ventilation during the application and drying period. Do not apply below 10°C. Application between 10 and 25°C and below 85% RH is desired. For best results do not apply more than 2 coats per day to reduce risk of timber swelling from excess moisture.

Coverage: 10 square metres per litre per coat. Coverage will vary dependent on surface porosity and profile.

Dry time (minimum): 2-3 hours at 18-25°C. Drying is slowed with lower temperatures. Do not apply at temperatures below 10°C or when temperatures are liable to drop below this during the drying period.

Recoat time (minimum): 3-4 hours.

Mix ratio: 10 parts Base to 1 part Cure (by volume). Refer to the Resene ProSelect mixing chart for additional details.

Mixing: Ensure Resene ProSelect Cure is mixed thoroughly before thinning. Mechanical stir. Do not shake.

Pot life: The mixed components must be used within 3 hours. At higher temperatures pot life is reduced.

Thinning: Required, thin 10% by volume of mixed product with clean water, Resene ProSelect XTend or Resene ProSelect Fast Set depending on application conditions.

Clean up: Water. DO NOT seal up left over mixtures within 12 hours after mixing due to potential carbon dioxide gas pressure build up.

Refer to www.resene.com/proselect or the Resene ProSelect Technical Data Booklet for more detailed information.



Resene ProSelect
info centre

Enjoy the Resene Promise of quality on premium paints. See your Resene ColorShop or the Resene website for a copy.

In every case it is recommended that the appropriate Data Sheet and Safety Data Sheet are consulted prior to application.

Resene

the paint the professionals use

In Australia: Resene Paints (Aust) Limited
7 Production Ave, PO Box 924, Beenheim, Qld 4207
Phone 1800 738 383 Fax 1800 064 960
Email advice@resene.com.au or visit www.resene.com.au

In New Zealand: Resene Paints Limited
Vogel Street, PO Box 38242, Wellington Mail Centre, Lower Hutt 5045
Phone (04) 577 0500 Fax (04) 577 0600
Email advice@resene.co.nz or visit www.resene.co.nz

Manufactured under a quality system certified as complying with ISO9001 by Telarc SA, an accredited certification body. Printed on environmentally responsible paper which complies with the requirements of environmental management systems EMAS and ISO14001, using vegetable-based inks.