

Resene product labels are updated from time to time. This label is provided as a guide for this product and may differ from the label on the container you purchase. Please discuss your project with your local Resene ColorShop team or reseller to ensure you have the right products to give you the best quality finish for your specific project.

net contents 500 mL
Must be mixed with the appropriate base.
Makes 5.5 litres when mixed with
5 litres of Resene Qristal ClearFloor Base. LL2481050H 5/24

SAFETY PRECAUTIONS

Read label before use. Keep out of reach of children. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage. Harmful if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause respiratory irritation. Harmful to aquatic life with long lasting effects.

PRECAUTIONS

DO NOT BREATHE MIST, VAPOURS OR SPRAY.
Store in original or correctly labelled container, tightly closed, in a well-ventilated area indoors, away from foodstuffs, at an ambient temperature and avoid freezing conditions. Store locked up. Use only outdoors or in a well-ventilated area. In case of inadequate ventilation wear respiratory protection. Wear protective gloves and clothing, eye and face protection. Wash all exposed external body areas thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment.

FIRST AID

IF SWALLOWED: Call a POISON CENTRE, doctor or first aider if you feel unwell.
IF INHALED: If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms call a POISON CENTRE, doctor or first aider.
IF ON SKIN (or hair): Wash with plenty of water. If skin irritation or rash occurs get medical advice. Take off contaminated clothing and wash before reuse.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so. Continue rinsing. If eye irritation persists get medical advice or attention.

If exposed or concerned get medical advice or attention.
IF MEDICAL ATTENTION IS REQUIRED: Have product container or label at hand. Further information can be obtained from
AUST: POISONS INFORMATION CENTRE 131 126 or call Resene 1800 738 383.
NZ: NATIONAL POISONS CENTRE 0800 POISON (764 766) or call Resene 0800 737 363.

CONTAINS: Hexamethylene Diisocyanate Polymer 10-60 g/L, Tridecanol Ethoxylated, Phosphated 10-120 g/L, Hexamethylene Diisocyanate Polymer, Ethoxylated 60-110 g/L, Hexamethylene-1,6-diisocyanate homopolymer 50-910 g/L.

For full technical instructions see Data Sheet D506A.

SPILLS: Eliminate all sources of ignition and use approved protective equipment. Absorb with sand or earth. Collect and seal in properly labelled drums. Do not allow to enter drains or run off into water ways. Refer to local waste management authority.

CLEANING PAINT EQUIPMENT: Remove paint from roller sleeve using a roller scraper and then brush/roll out as much paint as possible onto newspaper before washing out brushes or rollers with recommended clean up thinner. Do not allow washing residues to enter drains or run off into water ways. Refer to your local Council for disposal of dirty solvent borne thinners.

FIRE: Blanket flames with dry chemical, carbon dioxide or foam. Closed containers can explode when exposed to extreme heat.

DANGER

KEEP OUT OF REACH OF CHILDREN

Resene

Qristal ClearFloor 2K

waterborne flooring urethane

SATIN HARDENER

interior



Quick check

Name: Resene Qristal ClearFloor 2K Satin Hardener.

Mixing ratio: 10 parts Base: 1 part Satin Hardener (by volume).

Induction time: 10-15 minutes at 18°C.

Pot life: 4 hours at 18°C. DO NOT USE mixed product beyond pot life, mixed product will remain in a liquid state well beyond pot life.

Dry time (minimum): Tack free 1.5 hours at 18°C. Drying is affected by low temperatures, high humidity, and poor ventilation. Allow seven days for coating to reach full cure.

Recoat time (minimum): 2 hours at 18°C. Recoat when the applied coating is no longer milky in appearance and does not leave a fingerprint when pressed. Maximum: 3 days at 18°C.

Thinning: Do not thin, supplied at application viscosity.

Clean up: Warm water and detergent.

CONTAINS ISOCYANATES. When mixed with the correct base and sprayed, this PRODUCT MAY BE HARMFUL BY INHALATION. Do not breathe vapour or spray. Avoid contact with skin and eyes. Wear suitable protective clothing, gloves, eye and face protection including suitable breathing protection such as an air-supplied respirator or hood.

Do not mix Resene Qristal ClearFloor 2K with Resene Colour Enhance.

Enjoy the Resene Promise of quality on premium paints. See your Resene ColorShop or the Resene website for a copy. Read the appropriate Data Sheet and Safety Data Sheet before application.

Please ensure that use of this product is compatible with the substrate and surface preparation method and that the colour in this container is the same as selected. Resene does not accept any responsibility for the application of incorrect product to substrate or the application of incorrect colours. Resene products are designed to be used as a system for optimal results. Substitution may cause substandard results or system failure. For further painting advice and information, call 1800 738 383 (AUST), 0800 737 363 (NZ) or visit the Resene website.

Resene Qristal ClearFloor 2K is a two pack waterborne urethane durable flooring finish designed to protect your wooden flooring and keep it looking its best for longer.

General

- Read appropriate labels before use.
- Users of this product should familiarise themselves with the Code of Practice for the Safe Use of Isocyanates issued by OSH.
- Read the Safety Data Sheet (SDS) and product data sheet before use.
- This product comprises a Base and Hardener which must be mixed in the required ratio using a power mixer before application. Add the total contents of the Hardener container to the total contents of the base container. Once uniformly mixed allow to stand for the recommended induction time prior to use.
- Mixed product does not require thinning; thinning is detrimental to product performance.
- Drying is affected by low temperatures and high humidity.
- Use the mixed product within the stated pot life. The pot life of the mixed material is given for a specific temperature. Higher temperatures will reduce the pot life; conversely lower temperatures will increase it. Mixed product will remain liquid well past stated pot life. Application of mixed product beyond stated pot life will have a detrimental effect upon film formation, adhesion and performance.
- Substrate temperature should be 3°C above the "Dew Point".
- The "Dew Point" requirement can be presumed to be satisfied, if a thin clearly defined film of water applied to the cleaned surface with a damp cloth evaporates within 15 minutes.
- This product is designed for application to timber or timber composite flooring. If the surface you propose to coat is unsound or not referred to consult your nearest

Resene ColorShop or reseller for your nearest Resene Technical Representative.

Be PaintWise

For tips on responsible disposal of paint, cleaning equipment and minimising the impact of your decorating on the environment see the Resene website. Do not discharge any paint into the environment. Resene PaintWise (NZ) or paintback.com.au (Australia) accepts residual unwanted paint and packaging. Or contact your Local Authority for disposal information. Please recycle.



CAUTION

Do not tightly reseal quantities of leftover mixed product, as the mixed product generates carbon dioxide gas, which can cause the lid of a tightly sealed can to pop with force. Leave the mixed material in a safe place for at least 48 hours for outgassing to be completed before sealing cans for disposal through a Resene PaintWise location or approved hazard waste site.

Resene

the paint the professionals use

In Australia: Resene Paints (Aust) Limited
7 Production Ave, PO Box 918, Ashmore City, QLD 4214
Ph 1800 738 383 Visit resene.com.au

In New Zealand: Resene Paints Limited
Vogel St, Lower Hutt, PO Box 38-242, Wgtn Mail Centre
Ph (04) 577 0500 Visit resene.co.nz