

Resene product labels are updated from time to time. This label is provided as a guide for this product and may differ from the label on the container you purchase.
Please discuss your project with your local Resene ColorShop team or reseller to ensure you have the right products to give you the best quality finish for your specific project.

net contents
1 litre

LL81201 5/13

WARNING

Read label before use. Keep out of reach of children. Harmful if swallowed. Causes lung damage if swallowed. Causes skin and eye irritation. Suspected of damaging fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure. May cause respiratory irritation. Vapours may cause dizziness or drowsiness.

PRECAUTIONS

DO NOT BREATHE FUMES/MISTS/SPRAYS/VAPOURS. DO NOT EAT, DRINK OR SMOKE WHILE USING.

Do not handle until all safety precautions have been read and understood. Store in original or correctly labelled container, tightly closed, in a well ventilated area indoors, away from foodstuffs, either between 15°C-20°C or at a cool, constant temperature. Store locked up. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wash thoroughly after handling. Wear protective gloves and eye/face protection and respiratory protection. Dispose of empty container safely. Consult Resene checklist on environmentally acceptable methods for cleaning equipment and disposing of unwanted paint.

FIRST AID

IF SWALLOWED: Rinse mouth. Call a POISON CENTRE or doctor/physician if you feel unwell. IF ON SKIN (or hair): Wash with plenty of soap and water; If skin irritation occurs; Get medical advice. Take off contaminated clothing and wash before re-use. IF IN EYES: Rinse cautiously with water for

several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing.

IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory difficulties seek medical attention.

When seeking medical advice take this container with you.

If exposed or concerned: Call a POISON CENTRE. Further information can be obtained from AUST: POISONS INFORMATION CENTRE 131 126 or call Resene 1800 738 383.

NZ: NATIONAL POISONS CENTRE 0800 POISON (764 766) or call Resene 0800 737 363.

Contains: Methyl Benzene 410-450 gms/L.

For use as a paint thinner.

SPILLS

Eliminate all sources of ignition. Ventilate area, avoid breathing vapours.

Use absorbent clean-up materials, such as fire retardant treated sawdust or diatomaceous earth to dike and contain spill. Scrape up and remove. Collect and seal in properly labelled drums. Refer to local waste management authority. Keep out of public sewers and waterways.

FIRE

Blanket flames with dry chemical, carbon dioxide or foam. Wear self-contained breathing apparatus. Closed containers may explode when exposed to extreme heat.

The storage of flammable goods may require certification/licencing by the appropriate agency. Consult the local Dangerous Goods Inspectorate. Dispose of unwanted material in accordance with Local Body Regulations.

In every case it is recommended that the Safety Data Sheet is consulted prior to application.

Be PaintWise

For tips on minimising the impact of your decorating on the environment see the Resene website.

DANGER

KEEP OUT OF REACH OF CHILDREN

Resene Thinner No.12



Quick check

| Thinner | Product |
|---------------|--|
| Mineral Turps | Mica Bond |
| No.2 | Ceiling Velvet; Lusta-Glo; Room Velvet; Super Gloss; Sureseal |
| No.3A | ArmourZinc 125 |
| No.4 | Vinyl Etch |
| No.5 | Armourcote 608; Steel Fab |
| No.6 | Armourcote 210 and 510; Alumastic; Imperite I.F. 503; Armourchlor Series (spray application); ArmourZinc 110 |
| No.7A | Polymeric AV-8; Uracryl 400 Series (spray application) |
| No.8 | Uracryl 400 Series (brush/roller application) |
| No.9 | Zincilate 10 and 11 |
| No.10 | Slow Retarder; Rust-Arrest (brush/roller application) |
| No.11 | Brush/roller application – Armourchlor Series; ArmourZinc 110; Steel Fab. Armourcote 515 (application above 35°C or over zinc rich primers); Medium Retarder |
| No.12 | ArmourZinc 120; Armourcote 220, 512 and 515; Universal Cleaner; Rust-Arrest (spray application) |
| No.13 | Imperite 413 |
| No.15 | ArmourCat 800, 805, 822, 823, 842, 843 |
| No.16 | ArmourCat 810 Metallic Effects |

Refer to appropriate Product Data Sheet and Safety Data Sheet prior to application of, or clean up after use of, Resene Engineered Coating Systems products.

For further painting advice and information, call 1800 738 383 (AUST), 0800 737 363 (NZ) or visit the Resene website.

Resene

the paint the professionals use

In Australia: Resene Paints (Aust) Limited
7 Production Ave, PO Box 924, Beenleigh, Qld, 4207
Phone 1800 738 383 Fax 1800 064 960
Email advice@resene.com.au or visit www.resene.com.au

In New Zealand: Resene Paints Limited
Vogel Street, PO Box 38242, Wellington Mail Centre, Lower Hutt 5045
Phone (04) 577 0500 Fax (04) 577 0600
Email advice@resene.co.nz or visit www.resene.co.nz

Manufactured under a quality system certified as complying with ISO9001 by Telarc SAI, an accredited certification body. Printed on environmentally responsible paper, which complies with the requirements of environmental management systems EMAS and ISO14001, using vegetable-based inks.



UN NO. 1263 – PAINT
RELATED MATERIAL

Harmful if swallowed.
Causes skin and eye irritation.
May damage fertility or the unborn child.
May cause damage to organs.

HIGHLY FLAMMABLE LIQUID AND VAPOUR

Keep away from heat/sparks/
open flames/hot surfaces.
Keep closed when not in use.
No smoking.



Safety Data
Sheets