

RESENE CROWN ROOF

Resene Paints Ltd

Version No: 1.1
Safety Data Sheet according to the Health and Safety at Work (Hazardous Substances) Regulations 2017

Issue Date: 12/03/2021
Print Date: 12/03/2021
L.GHS.NZL.EN

SECTION 1 Identification of the substance / mixture and of the company / undertaking

Product Identifier

Product name	RESENE CROWN ROOF
Chemical Name	Not Applicable
Synonyms	Incl. Karaka, Grey Friars, Ironsand colours.
Other means of identification	Not Available

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	10808 10809 10810
--------------------------	-------------------

Details of the supplier of the safety data sheet

Registered company name	Resene Paints Ltd
Address	32-50 Vogel Street Wellington New Zealand
Telephone	+64 4 577 0500
Fax	+64 4 5773327
Website	www.resene.co.nz
Email	advice@resene.co.nz

Emergency telephone number

Association / Organisation	NZ POISONS (24hr 7 days)	CHEMWATCH EMERGENCY RESPONSE
Emergency telephone numbers	0800 764766	+61 2 9186 1132
Other emergency telephone numbers	Not Available	+64 800 700 112

Once connected and if the message is not in your preferred language then please dial 01

SECTION 2 Hazards identification

Classification of the substance or mixture

Classification [1]	Acute Aquatic Hazard Category 3
Legend:	1. Classified by Chemwatch; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI
Determined by Chemwatch using GHS/HSNO criteria	9.1D

Label elements

Hazard pictogram(s)	Not Applicable
Signal word	Not Applicable

Hazard statement(s)

H402	Harmful to aquatic life.
------	--------------------------

Precautionary statement(s) Prevention

P273	Avoid release to the environment.
------	-----------------------------------

Precautionary statement(s) Response

Not Applicable

Precautionary statement(s) Storage

Not Applicable

Precautionary statement(s) Disposal

P501	Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.
------	--

SECTION 3 Composition / information on ingredients

RESENE CROWN ROOF

Substances

See section below for composition of Mixtures

Ingredients are required by the Hazard Substances (Safety Data Sheets) Notice 2017 to be identified:

Mixtures

CAS No	%[weight]	Name
25265-77-4	1-3	2,2,4-trimethyl-1,3-pentanediol monoisobutyrate
84133-50-6	0.1-1	alcohols C12-14 secondary ethoxylated

SECTION 4 First aid measures**Description of first aid measures**

Eye Contact	<p>If this product comes in contact with eyes:</p> <ul style="list-style-type: none"> ▶ Wash out immediately with water. ▶ If irritation continues, seek medical attention. ▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	<p>If skin or hair contact occurs:</p> <ul style="list-style-type: none"> ▶ Flush skin and hair with running water (and soap if available). ▶ Seek medical attention in event of irritation.
Inhalation	<ul style="list-style-type: none"> ▶ If fumes, aerosols or combustion products are inhaled remove from contaminated area. ▶ Other measures are usually unnecessary.
Ingestion	<ul style="list-style-type: none"> ▶ Immediately give a glass of water. ▶ First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor. ▶ If spontaneous vomiting appears imminent or occurs, hold patient's head down, lower than their hips to help avoid possible aspiration of vomitus.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 Firefighting measures**Extinguishing media**

- ▶ Alcohol stable foam.

Special hazards arising from the substrate or mixture

Fire Incompatibility	▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches.
-----------------------------	--

Advice for firefighters

Fire Fighting	▶ Alert Fire Brigade and tell them location and nature of hazard.
Fire/Explosion Hazard	<ul style="list-style-type: none"> ▶ Non combustible. <p>Burning release: carbon dioxide (CO₂) other pyrolysis products typical of burning organic material. May emit poisonous fumes.</p>

SECTION 6 Accidental release measures**Personal precautions, protective equipment and emergency procedures**

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	Control personal contact with the substance, by using personal protective equipment. Contain spill with sawdust, sand, earth, inert material or vermiculite then place in suitable, labelled container for waste disposal. Wipe up. Clean area with large quantity of water to complete clean-up.
Major Spills	Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard. Wear appropriate personnel protective equipment and clothing to prevent exposure. Avoid breathing in mists or vapours and skin or eyes contact. Prevent, by any means available, spillage from entering drains or water course. Stop leak if safe to do so. Contain spill with sawdust, sand, earth, inert material or vermiculite then place in suitable, labelled container for waste disposal. Wipe up. Wash area and prevent runoff into drains. If contamination of drains or waterways occurs, advise emergency services.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

Continued...

RESENE CROWN ROOF

Precautions for safe handling

Safe handling	▶ Avoid unnecessary personal contact.
Other information	▶ Store in original containers.

Conditions for safe storage, including any incompatibilities

Suitable container	▶ Packaging as recommended by manufacturer.
Storage incompatibility	▶ strong oxidisers

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL)

INGREDIENT DATA

Not Available

Emergency Limits

Ingredient	TEEL-1	TEEL-2	TEEL-3
2,2,4-trimethyl-1,3-pentanediol monoisobutyrate	13 mg/m ³	140 mg/m ³	840 mg/m ³

Ingredient	Original IDLH	Revised IDLH
2,2,4-trimethyl-1,3-pentanediol monoisobutyrate	Not Available	Not Available
alcohols C12-14 secondary ethoxylated	Not Available	Not Available

Occupational Exposure Banding


Ingredient	Occupational Exposure Band Rating	Occupational Exposure Band Limit
alcohols C12-14 secondary ethoxylated	E	≤ 0.1 ppm

Notes:

Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health.

MATERIAL DATA

Exposure controls

Appropriate engineering controls	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard.
Personal protection	
Eye and face protection	▶ Safety glasses with side shields ▶ Chemical goggles.
Skin protection	See Hand protection below
Hands/feet protection	The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. ▶ Wear chemical protective gloves, e.g. PVC.
Body protection	See Other protection below
Other protection	▶ Overalls.

Respiratory protection

Respiratory protection required in insufficiently ventilated working areas. An approved respirator with a replaceable vapour/ mist filter should be used. Refer to relevant regulations for further information concerning respiratory protective requirements. Reference should be made to AS/NZS 1715 Standard, Selection, Use and Maintenance of Respiratory Protective Devices; and AS/NZS 1716 Standard, Respiratory Protective Devices, in order to make any necessary changes for individual circumstances. Recommended filter type: Type A filter (organic vapour).

SECTION 9 Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Coloured acrylic dispersion
------------	-----------------------------

RESENE CROWN ROOF

Physical state	Liquid	Relative density (Water = 1)	1.08-1.11
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	8.2-9.2	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	1000-2000
Initial boiling point and boiling range (°C)	100	Molecular weight (g/mol)	Not Available
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	65
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Miscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	30

SECTION 10 Stability and reactivity

Reactivity	See section 7
Chemical stability	▶ stable.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 Toxicological information

Information on toxicological effects

Inhaled	The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models).
Ingestion	The material has NOT been classified by EC Directives or other classification systems as 'harmful by ingestion'.
Skin Contact	The material is not thought to produce adverse health effects or skin irritation following contact (as classified by EC Directives using animal models). Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream through, for example, cuts, abrasions, puncture wounds or lesions, may produce systemic injury with harmful effects.
Eye	Although the liquid is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn).
Chronic	Repeated or long-term occupational exposure is likely to produce cumulative health effects.

RESENE CROWN ROOF	TOXICITY	IRRITATION
	Not Available	Not Available
2,2,4-trimethyl-1,3-pentanediol monoisobutyrate	TOXICITY	IRRITATION
	dermal (guinea pig) LD50: >19 mg/kg ^[2]	Eye: no adverse effect observed (not irritating) ^[1]
	Oral(Rat) LD50; >3200 mg/kg ^[2]	Eyes - Moderate irritant *
		Skin - Slight irritant *
		Skin (rabbit): mild *** Skin: no adverse effect observed (not irritating) ^[1]
alcohols C12-14 secondary ethoxylated	TOXICITY	IRRITATION
	Not Available	Not Available

Legend:

1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. * Value obtained from manufacturer's SDS. Unless otherwise

Continued...

RESENE CROWN ROOF

specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

RESENE CROWN ROOF	Generally, linear and branched-chain alkyl esters are hydrolysed to their component alcohols and carboxylic acids in the intestinal tract, blood and most tissues throughout the body.
2,2,4-TRIMETHYL-1,3-PENTANEDIOL MONOISOBUTYRATE	Not a skin sensitiser (guinea pig, Magnusson-Kligman) *** Ames Test: negative *** Micronucleus, mouse: negative *** Not mutagenic *** No effects on fertility or foetal development seen in the rat *** * [SWIFT] ** [Eastman] *** [Perstop] The material may be irritating to the eye, with prolonged contact causing inflammation. The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic).
ALCOHOLS C12-14 SECONDARY ETHOXYLATED	No significant acute toxicological data identified in literature search. Polyethers, for example, ethoxylated surfactants and polyethylene glycols, are highly susceptible towards air oxidation as the ether oxygens will stabilize intermediary radicals involved. Human beings have regular contact with alcohol ethoxylates through a variety of industrial and consumer products such as soaps, detergents, and other cleaning products . Alcohol ethoxylates are according to CESIO (2000) classified as Irritant or Harmful depending on the number of EO-units: EO < 5 gives Irritant (Xi) with R38 (Irritating to skin) and R41 (Risk of serious damage to eyes) EO > 5-15 gives Harmful (Xn) with R22 (Harmful if swallowed) - R38/41 EO > 15-20 gives Harmful (Xn) with R22-41 >20 EO is not classified (CESIO 2000) Oxo-AE, C13 EO10 and C13 EO15, are Irritating (Xi) with R36/38 (Irritating to eyes and skin) . AE are not included in Annex 1 of the list of dangerous substances of the Council Directive 67/548/EEC In general, alcohol ethoxylates (AE) are readily absorbed through the skin of guinea pigs and rats and through the gastrointestinal mucosa of rats. For high boiling ethylene glycol ethers (typically triethylene- and tetraethylene glycol ethers): Skin absorption: Available skin absorption data for triethylene glycol ether (TGBE), triethylene glycol methyl ether (TGME), and triethylene glycol ethylene ether (TGEE) suggest that the rate of absorption in skin of these three glycol ethers is 22 to 34 micrograms/cm ² /hr, with the methyl ether having the highest permeation constant and the butyl ether having the lowest.

Acute Toxicity	✗	Carcinogenicity	✗
Skin Irritation/Corrosion	✗	Reproductivity	✗
Serious Eye Damage/Irritation	✗	STOT - Single Exposure	✗
Respiratory or Skin sensitisation	✗	STOT - Repeated Exposure	✗
Mutagenicity	✗	Aspiration Hazard	✗

Legend: ✗ – Data either not available or does not fill the criteria for classification
✔ – Data available to make classification

SECTION 12 Ecological information

Toxicity

RESENE CROWN ROOF	Endpoint	Test Duration (hr)	Species	Value	Source
	Not Available	Not Available	Not Available	Not Available	Not Available
2,2,4-trimethyl-1,3-pentanediol monoisobutyrate	Endpoint	Test Duration (hr)	Species	Value	Source
	EC50	48	Crustacea	>19mg/l	2
	LC50	96	Fish	>19mg/l	2
	NOEC(ECx)	72	Algae or other aquatic plants	3.28mg/l	1
	EC50	72	Algae or other aquatic plants	18.4mg/l	1
alcohols C12-14 secondary ethoxylated	Endpoint	Test Duration (hr)	Species	Value	Source
	Not Available	Not Available	Not Available	Not Available	Not Available
Legend:	Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 (QSAR) - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data				

Harmful to aquatic organisms.
DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
2,2,4-trimethyl-1,3-pentanediol monoisobutyrate	LOW	LOW

Bioaccumulative potential

Ingredient	Bioaccumulation
2,2,4-trimethyl-1,3-pentanediol monoisobutyrate	LOW (LogKOW = 2.9966)

Mobility in soil

Continued...

RESENE CROWN ROOF

Ingredient	Mobility
2,2,4-trimethyl-1,3-pentanediol monoisobutyrate	LOW (KOC = 22.28)

SECTION 13 Disposal considerations

Waste treatment methods

Product / Packaging disposal	
	<p>Legislation addressing waste disposal requirements may differ by country, state and/ or territory.</p> <ul style="list-style-type: none"> ▶ DO NOT allow wash water from cleaning or process equipment to enter drains. ▶ Recycle wherever possible or consult manufacturer for recycling options. <p>Consult manufacturer for recycling option. Resene Paintwise accepts residual unwanted paint and packaging. See Resene website for Paintwise information. Or contact a Local Authority for the disposal information. Do not discharge the substance into the environment.</p>

Ensure that the hazardous substance is disposed in accordance with the Hazardous Substances (Disposal) Notice 2017

Disposal Requirements

Packages that have been in direct contact with the hazardous substance must be only disposed if the hazardous substance was appropriately removed and cleaned out from the package.

SECTION 14 Transport information

Labels Required

Marine Pollutant	NO
HAZCHEM	Not Applicable

Land transport (ADG): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
2,2,4-trimethyl-1,3-pentanediol monoisobutyrate	Not Available
alcohols C12-14 secondary ethoxylated	Not Available

Transport in bulk in accordance with the ICG Code

Product name	Ship Type
2,2,4-trimethyl-1,3-pentanediol monoisobutyrate	Not Available
alcohols C12-14 secondary ethoxylated	Not Available

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

This substance is to be managed using the conditions specified in an applicable Group Standard

HSR Number	Group Standard
HSR002670	Surface Coatings and Colourants (Subsidiary Hazard) Group Standard 2017

2,2,4-trimethyl-1,3-pentanediol monoisobutyrate is found on the following regulatory lists

New Zealand Approved Hazardous Substances with controls
New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data
New Zealand Inventory of Chemicals (NZIoC)

alcohols C12-14 secondary ethoxylated is found on the following regulatory lists

New Zealand Approved Hazardous Substances with controls
New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data
New Zealand Inventory of Chemicals (NZIoC)

Hazardous Substance Location

Subject to the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Hazard Class	Quantities
Not Applicable	Not Applicable

RESENE CROWN ROOF

Certified Handler

Subject to Part 4 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Class of substance	Quantities
Not Applicable	Not Applicable

Refer Group Standards for further information

Maximum quantities of certain hazardous substances permitted on passenger service vehicles

Subject to Regulation 13.14 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Hazard Class	Gas (aggregate water capacity in mL)	Liquid (L)	Solid (kg)	Maximum quantity per package for each classification
Not Applicable	Not Applicable	Not Applicable	Not Applicable	Not Applicable

Tracking Requirements

Not Applicable

National Inventory Status

National Inventory	Status
Australia - AIC / Australia Non-Industrial Use	Yes
New Zealand - NZIoC	Yes
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory and are not exempt from listing (see specific ingredients in brackets)

SECTION 16 Other information

Revision Date	12/03/2021
Initial Date	08/11/2019

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment.

Definitions and abbreviations

PC—TWA: Permissible Concentration-Time Weighted Average
 PC—STEL: Permissible Concentration-Short Term Exposure Limit
 IARC: International Agency for Research on Cancer
 ACGIH: American Conference of Governmental Industrial Hygienists
 STEL: Short Term Exposure Limit
 TEEL: Temporary Emergency Exposure Limit.
 IDLH: Immediately Dangerous to Life or Health Concentrations
 OSF: Odour Safety Factor
 NOAEL :No Observed Adverse Effect Level
 LOAEL: Lowest Observed Adverse Effect Level
 TLV: Threshold Limit Value
 LOD: Limit Of Detection
 OTV: Odour Threshold Value
 BCF: BioConcentration Factors
 BEI: Biological Exposure Index

Powered by AuthorITe, from Chemwatch.