

Resene product labels are updated from time to time. This label is provided as a guide for this product and may differ from the label on the container you purchase. Please discuss your project with your local Resene ColorShop team or reseller to ensure you have the right products to give you the best quality finish for your specific project.

# Resene

## AquaLAQ Colour Coat

furniture, joinery, cabinetry finish

interior waterborne satin



### WARNING

KEEP OUT OF REACH OF CHILDREN

LL1570201F 11/18



9 418022 070535

## net contents 1 litre

LL1570201B 11/18

### SAFETY PRECAUTIONS

Read label before use. Keep out reach of children. Causes skin irritation. Causes serious eye irritation. Harmful to aquatic life with long lasting effects.

### PRECAUTIONS

USE WITH ADEQUATE VENTILATION. DO NOT EAT, DRINK OR SMOKE WHILE USING. Store in original or correctly labelled container, tightly closed, in a well-ventilated area indoors, away from foodstuffs, at an ambient temperature and avoid freezing conditions. Wear protective gloves and clothing, eye and face protection. Avoid release to the environment.

### FIRST AID

IF SWALLOWED: Rinse mouth. Call a POISON CENTRE, doctor or physician if you feel unwell.

IF ON SKIN (or hair): Rinse skin with plenty of soap and water. If skin irritation or rash occurs get medical attention or advice. Take off contaminated clothing and wash before reuse.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so. Continue rinsing. If eye irritation persists get medical attention or advice.

When seeking medical advice take this container with you.

Further information can be obtained from AUST: POISONS INFORMATION CENTRE 131 126 or call Resene 1800 738 383.

NZ: NATIONAL POISONS CENTRE 0800 POISON (764 766) or call Resene 0800 737 363.

For use as a decorative/protective coating.

**SPILLS:** Wear appropriate protective clothing. Absorb with sand or earth. Collect and seal in properly labelled drums. Do not allow to enter drains or to run off into waterways. Refer to local waste management authority.

**CLEANING PAINT EQUIPMENT:** Use approved waterbased cleaning systems and processes to clean all equipment. Dispose of all waste water and product in an approved manner.

Resene AquaLAQ Colour Coat is a single pack waterborne acrylic, using the latest waterborne technology, designed for kitchens, shop fittings and furniture finishing. Easy to use and fast drying to an extremely durable finish. The rheology of Resene AquaLAQ minimises applicator error. Resene AquaLAQ can be touched up when necessary with excellent sandability.

### Preparation

- Ensure substrates to be coated are in sound condition, dry, free from dirt, dust, loose material, oil (including mineral oil based wood finishes or similar) and salt.
- **All sanding dusts may be harmful and appropriate protection must be worn. In particular dusts from old lead or chromate based paints or old building materials containing asbestos may be injurious to health if inhaled or ingested. Seek expert advice if the presence of these materials is suspected.**
- For new work ensure the surface is sanded to a smooth finish and dusted off. Round all sharp edges. Ensure the surface is dry before painting.
- This product may be used to paint a wide variety of surfaces. If the surface you propose to paint is unsound or not referred to, try a small test area first or contact your local Resene ColorShop or reseller for advice.

### Priming

- Sand all wood substrates, then prime/seal with Resene AquaLAQ Quick Dry Sealer or Resene AquaLAQ NGR Primer Sealer.
- Repaints - sppt prime all bare areas with the same primer shown for new work and proceed as for new work.

### Application

- Ensure you have read the detailed Resene AquaLAQ application sheet available from Resene prior to application of product.
- Apply 1-2 coats by spray in the required colour allowing at least 1 hour before recoating.
- Maintain good ventilation throughout the drying and post application curing period to ensure the paint is properly cured. This may require use of an extraction system. Multiple air changes are required during application and until product is cured sufficiently. Ensure humidity is less than 65% and temperature 15-25°C for ideal application and curing. Poor ventilation may affect appearance and performance.
- For extra protection or to change the final gloss level, apply Resene AquaLAQ Clear Coat as the finish coat.

### Maintenance (after a minimum of four weeks' drying)

See the Resene Caring for your paint finish brochure or the Resene website for full cleaning instructions.

### Be PaintWise

For tips on responsible disposal of paint, cleaning equipment and minimising the impact of your decorating on the environment see the Resene website. Do not discharge any paint into the environment. Resene PaintWise accepts residual unpainted paint and packaging. Or contact your Local Authority for disposal information.

Please ensure that use of this product is compatible with the substrate and surface preparation method and that the colour in this container is the same as selected. Resene does not accept any responsibility for the application of incorrect product to substrate or the application of incorrect colours. Resene products are designed to be used as a system for optimal results. Substitution may cause substandard results or system failure. For further painting advice and information, call 1800 738 383 (AUST), 0800 737 363 (NZ) or visit the Resene website.



## Quick check

**Use on:** Kitchens, shop fittings and furniture finishing, over correctly prepared MDF board and wood substrates. May also be used on window joinery.

**Gloss level:** Satin. Other gloss levels available with application of Resene AquaLAQ Clear Coat.

**Coverage:** 8-10 square metres per litre per coat. The spreading rate recommended for this product will achieve hiding in two coats for most colours. Increased spreading rates can be used but additional coats may be needed to achieve required film build and hiding. See the Resene website for more information.

**Dry time (minimum):** Touch dry 10-15 minutes. Maintain good ventilation throughout the drying and post application curing period to ensure the paint is properly cured. This may require use of an extraction system. Multiple air changes are required during application and until product is cured sufficiently. Ensure humidity is less than 65% and temperature 15-25°C for ideal application and curing. Poor ventilation may affect appearance and performance.

**Recoat time (minimum):** 1 hour.

**Serviceable after:** While the coating is serviceable after 48 hours depending on film thickness, tinter level and drying conditions, it will still be in the curing stage so care needs to be taken with contact and wiping.

**Primer required:** Yes.

**Usual number of coats:** 1-2.

**Application method:** Spray - pressure pot, suction or gravity.

**Thinning:** Do not thin. Consult Resene if needed.

**Clean up:** Water.

**Colour range:** Selected Resene Total Colour System including BS5252, Multi-finish, Whites & Neutrals and The Range.

**Before use:** Stir well with a wide flat stirrer, mixing from the bottom of the pail towards the top.

Enjoy the Resene Promise of quality on premium paints. See your Resene ColorShop or the Resene website for a copy. In every case it is recommended that the appropriate Data Sheet and Safety Data Sheet are consulted prior to application.

# Resene

the paint the professionals use

# Resene

Automotive & Light Industrial

In Australia: Resene Paints (Aust) Limited  
7 Production Ave, PO Box 924, Beenleigh, QLD 4207  
Ph 1800 738 383 Visit [www.resene.com.au](http://www.resene.com.au)

In New Zealand: Resene Paints Limited  
Vogel St, PO Box 38242, Vighi Mail Centre, Lower Hutt 5045  
Ph (04) 577 0500 Visit [www.resene.co.nz](http://www.resene.co.nz)

Resene Automotive & Light Industrial  
PO Box 62282, Mt Wellington Mail Centre, Auckland 1060  
Call (09) 259 2738, Fax (09) 259 2937  
visit [www.rail.co.nz](http://www.rail.co.nz) or email us at [info@rail.co.nz](mailto:info@rail.co.nz)

Manufactured under a quality system certified as complying with ISO9001 by Talcir SAJ, an accredited certification body. Printed on environmentally responsible paper, which meets with the requirements of environmental management system EMAS. Printed using de-inkable toners for recycling with no solvent emissions.