

Resene product labels are updated from time to time. This label is provided as a guide for this product and may differ from the label on the container you purchase.

Please discuss your project with your local Resene ColorShop team or reseller to ensure you have the right products to give you the best quality finish for your specific project.

KEEP OUT OF REACH OF CHILDREN

# Resene Broadwall Surface Prep & Seal

interior

A-LL39504 10/23

#### SAFETY PRECAUTIONS

Read label before use. Keep out of reach of children. This material is quite bland; with vapour, occasional skin contact and even minor ingestion having negligible hazard. Repeated skin contact may, and any eye contact will, cause irritation. Harmful to aquatic life with long lasting effects.

#### PRECAUTIONS

USE WITH ADEQUATE VENTILATION. DO NOT EAT, DRINK OR SMOKE WHILE USING.

Store in original or correctly labelled container, tightly closed, in a well-ventilated area indoors, away from foodstuffs, at an ambient temperature and avoid freezing conditions. Avoid release to the environment.

#### FIRST AID

IF SWALLOWED: Call a POISON CENTRE, doctor or first aider if you feel unwell.

IF INHALED: If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing.

IF ON SKIN (or hair): Rinse skin with plenty of soap and water. If skin irritation or rash occurs get medical advice or attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing. If eye irritation persists get medical advice or attention.

When seeking medical advice take this container with you.

Further information can be obtained from  
AUST: POISONS INFORMATION CENTRE 131 126  
or call Resene 1800 738 383.

NZ: NATIONAL POISONS CENTRE 0800 POISON (764 766)  
or call Resene 0800 737 363.

For use as an interior surface preparation coating.  
For full technical instructions see Data Sheet D807.

**SPILLS:** Wear appropriate protective clothing. Absorb with sand or earth. Collect and seal in properly labelled drums. Do not allow to enter drains or to run off into waterways. Refer to local waste management authority.

**CLEANING PAINT EQUIPMENT:** Brush/roll out as much paint as possible onto newspaper before washing brushes and rollers. Dispose of wash-up water onto grassy/unsealed area or into inside sink/basin, NOT into outside stormwater drain where it may harm fish in local waterways.

Suitable for achieving a level 5 finish. Recommended by GIB®.



Resene Broadwall Surface Prep & Seal is a high build basecoat designed for roller application over stopped and jointed wall systems. It equalises surface porosities, smooths minor surface irregularities, minimises textural differences, seals the surface and provides a perfect base for subsequent Resene finishes. Resene Broadwall Surface Prep & Seal is a key element to achieving a Level 5 finish on plasterboard.

#### Preparation

- Ensure surfaces to be painted are dry, free from dust, grease, loose material and weak, powdery or uncured jointing compound.
- Fill cracks and holes with an appropriate filler before painting.
- Where staining is present the source of staining must be removed.
- Remove excess jointing compounds where possible by sanding down to a smooth surface and wipe with a damp cloth to remove dust.
- When preparing plasterboard, avoid sanding the paper as this will cause furring and unacceptable textural differences in the finish.
- Where the paper surface has yellowed due to prolonged exposure to light or is stained, use Resene Sureseal (see Data Sheet D42).
- Prepare plasterboard to an appropriate level of finish. Resene Broadwall Surface Prep & Seal is recommended for critical lighting areas.
- For surface reinstatement after stripping wallpaper, apply Resene Sureseal, allow to dry and lightly sand, before applying Resene Broadwall Surface Prep & Seal.

**All sanding dusts may be harmful and appropriate protection must be worn. In particular dusts from old lead or chromate-based paints or old building materials containing asbestos may be injurious to health if inhaled or ingested. Seek expert advice if the presence of these materials is suspected.**

This product is typically used on new stopped plaster and plasterboard. If the surface you propose to coat is unsound or not referred to, try a small test area first or contact your local Resene ColorShop or reseller for advice.

#### Application

- Resene Broadwall Surface Prep & Seal may be applied by roller using a High

net contents 4 litres

Solids (Resene No.15) sleeve or brush (touch up or cutting in). Roller or brush will leave some texture that will require additional sanding to make smooth.

- Apply a full coat of Resene Broadwall Surface Prep & Seal at the recommended spreading rate. Lightly sand with a pole sander to produce a smooth surface and wipe with a clean, damp sponge to remove dust.
- Reinforcement of Resene Broadwall Surface Prep & Seal with a full coat of Resene Sureseal is recommended for service areas, such as bathrooms, kitchens and wet areas.
- When overcoating with waterborne paints, the coverage of that first coat may vary with application method, technique and temperature. If necessary, thin it with up to 10% clean tap water to maintain recommended coverage.
- Maintain good ventilation throughout the drying and curing period to ensure the coating is properly cured. Poor ventilation may inhibit curing and performance.
- Wear a well-fitted dust mask when sanding Resene Broadwall Surface Prep & Seal.

#### Be PaintWise

For tips on responsible disposal of paint, cleaning equipment and minimising the impact of your decorating on the environment see the Resene website. Do not discharge any paint into the environment. Resene PaintWise (NZ) or paintback.com.au (Australia) accepts residual unwanted paint and packaging. Or contact your Local Authority for disposal information. Please recycle.



**Resene**  
the paint the professionals use

In Australia: Resene Paints (Aust) Limited  
7 Production Ave, PO Box 918, Ashmore City, QLD 4214  
Ph 1800 738 383 Visit resene.com.au

In New Zealand: Resene Paints Limited  
Vogel St, PO Box 38242, Wgtn Mail Centre, Lower Hutt 5045  
Ph (04) 577 0500 Visit resene.co.nz



#### Quick check

**Use on:** Interior plasterboard, jointing compounds, MDF and Pine.

**Gloss level:** Flat.

**Coverage:** Up to 4 square metres per litre per coat, dependent on surface porosity.

**Dry time:** 6 hours. Do not apply at temperatures below 10°C or when temperatures are liable to drop below this during drying period. Drying is slowed by low temperatures and high humidity. Do not apply under damp conditions.

**Recoat time (minimum):** 6 hours.

**Number of coats:** Usually one.

**Application method:** High Solids roller sleeve (Resene No.15) or brush (touch up or cutting in).

**Colour:** Off-white when dry.

**Before use:** Stir well with a wide flat stirrer.

**Clean up:** Water.

Enjoy the Resene Promise of quality on premium paints. See your Resene ColorShop or the Resene website for a copy.

In every case it is recommended that the appropriate Data Sheet and Safety Data Sheet are consulted prior to application.

Please ensure that use of this product is compatible with the substrate and surface preparation method and that the colour in this container is the same as selected. Resene does not accept any responsibility for the application of incorrect product to substrate or the application of incorrect colours. Resene products are designed to be used as a system for optimal results. Substitution may cause substandard results or system failure. For further painting advice and information, call 1800 738 383 (AUST), 0800 737 363 (NZ) or visit the Resene website.