

Resene product labels are updated from time to time. This label is provided as a guide for this product and may differ from the label on the container you purchase.  
Please discuss your project with your local Resene ColorShop team or reseller to ensure you have the right products to give you the best quality finish for your specific project.

## net contents 1 litre

Must be mixed with the appropriate Resene ProSelect Base.  
Makes 11L when mixed with 10L of Resene ProSelect Base. LL2750001H 10/17

### SAFETY PRECAUTIONS

Read label before use. Keep out of reach of children. Causes serious eye irritation. Causes mild skin irritation. May cause an allergic skin reaction. May cause allergy or asthma symptoms or breathing difficulties if inhaled. Causes damage to organs through prolonged or repeated exposure. Harmful to aquatic life.

### PRECAUTIONS

DO NOT BREATHE DUST, FUMES, GAS, MISTS, VAPOURS, SPRAYS. DO NOT EAT, DRINK OR SMOKE WHEN USING THIS PRODUCT. Store in original or correctly labelled container, tightly closed, in a well ventilated area indoors, away from foodstuffs, either between 15°C-20°C or at a cool, constant temperature. Wear protective gloves and clothing, eye and face protection. In case of inadequate ventilation wear respiratory protection. Avoid release to the environment. Ground or bond container and receiving equipment. Use explosion-proof electrical, ventilating, lighting and intrinsically safe equipment. Use only non-sparking tools. Dispose of empty container safely. Consult Resene checklist on environmentally acceptable methods for cleaning equipment and disposing of unwanted paint.

### FIRST AID

IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms, call a POISON CENTRE, doctor or physician.

IF SWALLOWED: Immediately call a POISON CENTRE, doctor, physician or first aider.

IF ON SKIN (or hair): Wash with plenty of soap and water. If skin irritation or rash occurs, get medical advice or attention. Wash contaminated clothing before reuse.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so. Continue rinsing. If eye irritation persists, get medical advice or attention.

Get medical advice or attention if you feel unwell.

If medical advice is required have product container or label at hand.

Further information can be obtained from  
AUST: POISONS INFORMATION CENTRE 131 126  
or call Resene 1800 738 383.

NZ: NATIONAL POISONS CENTRE 0800 POISON (764 766)  
or call Resene 0800 737 363.

For use by professional flooring contractors.

CONTAINS: Hexamethylene Diisocyanate 1-15 gms/L, Aliphatic Polyisocyanate >1000gms/L.

**SPILLS:** Wear appropriate protective clothing. Absorb with sand or earth. Collect and seal in properly labelled drums. Do not allow to enter drains or to run off into waterways. Refer to local waste management authority.

**CLEANING APPLICATION EQUIPMENT:** Brush/roll out as much product as possible onto newspaper before washing brushes and rollers. Dispose of wash-up water onto grassy/unsealed area or into inside sink/basin, NOT into outside stormwater drain where it may harm fish in local waterways..

**FIRE:** Use foam, CO<sub>2</sub>, dry chemical for extinction.

# Resene

## ProSelect

professional timber  
flooring finish  
blending system

## Cure

HARDENER

## DANGER

KEEP OUT OF REACH OF CHILDREN



Developed specifically for professional flooring contractors, Resene ProSelect Cure is an isocyanate hardener for use in the Resene ProSelect Blending System.

### FOR PROFESSIONAL USE ONLY

**Important note:** All processes for hardwood timber floor coating from the initial consultation with the client, through to final application/finishing and maintenance should follow the guidelines set out in the Australasian Timber Flooring Association (ATFA) Information Guide Manual and Web Site, [www.atfa.com.au](http://www.atfa.com.au).

**Mix ratio:** 10 parts Base to 1 part Cure (by volume). Refer to the Resene ProSelect Mixing Chart for additional details.

**Mixing:** Ensure Resene ProSelect Cure is mixed thoroughly before thinning. Mechanical stir. Do not shake.

**Clean up:** Water. DO NOT seal up left over mixtures within 12 hours after mixing due to potential carbon dioxide gas pressure build up.

### Not suitable for spray application.

Users of this product should be familiar with the Approved Code of Practice (ACOP) for the safe use of Isocyanates issued by WORKSAFE.

Refer to [www.resene.co.nz/proselect](http://www.resene.co.nz/proselect) or the Resene ProSelect Technical Data Booklet for more detailed information.

Enjoy the Resene Promise of quality on premium paints. See your Resene ColorShop or the Resene website for a copy.

In every case it is recommended that the appropriate Data Sheet and Safety Data Sheet are consulted prior to application.



UN NO. 1263 - PAINT RELATED MATERIAL

**FLAMMABLE LIQUID AND VAPOUR**  
Keep away from heat, sparks, open flames and hot surfaces. No smoking.

# Resene

the paint the professionals use

In Australia: Resene Paints (Aust) Limited  
7 Production Ave, PO Box 924, Beenleigh, Qld 4207  
Phone 1800 738 383 Fax 1800 064 960  
Email [advice@resene.com.au](mailto:advice@resene.com.au) or visit [www.resene.com.au](http://www.resene.com.au)

In New Zealand: Resene Paints Limited  
Vogel Street, PO Box 38242, Wellington Mail Centre, Lower Hutt 5045  
Phone (04) 577 0500 Fax (04) 577 0600  
Email [advice@resene.co.nz](mailto:advice@resene.co.nz) or visit [www.resene.co.nz](http://www.resene.co.nz)

Manufactured under a quality system certified as complying with ISO9001 by Telarc SA, an accredited certification body. Printed on environmentally responsible paper, which complies with the requirements of environmental management systems EMAS and ISO14001, using vegetable-based inks.

Please ensure that use of this product is compatible with the substrate and surface preparation method. Resene does not accept any responsibility for the application of incorrect product to substrate or the application of incorrect colours. Resene products are designed to be used as a system for optimal results. Substitution may cause substandard results or system failure. For further painting advice and information, call 1800 738 383 (AUST), 0800 737 363 (NZ) or visit the Resene website.