

Resene product labels are updated from time to time. This label is provided as a guide for this product and may differ from the label on the container you purchase.

Please discuss your project with your local Resene ColorShop team or reseller to ensure you have the right products to give you the best quality finish for your specific project.

KEEP OUT OF REACH OF CHILDREN

Resene ROCKCOTE

Resitex elastomeric textured coating exterior/interior

net contents
4 litres
tinter included

A-LL70704 5/12

WARNING

Read label before use. Keep out reach of children. This material is quite bland; with vapour, occasional skin contact and even minor ingestion having negligible hazard.

PRECAUTIONS

USE WITH ADEQUATE VENTILATION. DO NOT EAT, DRINK OR SMOKE WHILE USING.

Store in original or correctly labelled container, tightly closed, in a well ventilated area indoors, away from foodstuffs, either between 15°C-20°C or at a cool, constant temperature. Dispose of empty container safely. Consult Resene checklist on environmentally acceptable methods of cleaning equipment and disposing of unwanted paint. Do not contaminate any water supply.

FIRST AID

IF SWALLOWED: Rinse mouth. Call a POISON CENTRE or doctor/physician if you feel unwell.

IF ON SKIN (or hair): Remove/take off all contaminated clothing and wash before re-use. Wash skin with plenty of soap and water/shower. If skin irritation or rash occurs get medical advice/attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing. If eye irritation persists, get medical advice/attention.

When seeking medical advice take this container with you.

Further information can be obtained from AUST: POISONS INFORMATION CENTRE 131 126 or call Resene 1800 738 383.

NZ: NATIONAL POISONS CENTRE 0800 POISON (764 766) or call Resene 0800 737 363.

For use as a decorative/protective coating. For full technical instructions see Data Sheet D70.

SPILLS: Wear appropriate protective clothing. Absorb with sand or earth. Collect and seal in properly labelled drums. Do not allow to enter drains or to run off into waterways. Refer to local waste management authority.

CLEANING PAINT EQUIPMENT:

Brush/roll out as much paint as possible onto newspaper before washing brushes and rollers. Dispose of wash-up water onto grassy/unsealed area or into inside sink/basin, NOT into outside stormwater drain where it may harm fish in local waterways.

Resene Rockcote Resitex is a tough elastomeric acrylic texture finish for beautifying and protecting concrete structures. Available in four grades: **Coarse**, a 3mm deeply textured grade with a rugged appearance and the ability to upgrade rough substrata; **Medium**, a 1.4mm Mediterranean style texture; **Standard**, an 800 micron texture with universal appeal; **Plastercote**, for a smoother and troweled finish. May be overcoated with Resene Multishield+ for added durability and a hard surface that is self-cleaning. Resene Resitex Plastercote is an elastomeric waterborne specialist finish perfect for creating a Mediterranean style effect, yet tough enough to withstand the harsh environment. Ideally suited for structures that will flex and develop minor cracks.

Preparation

- Ensure surfaces to be coated are in sound condition, dry, free from dirt, dust, loose material and salt.
- If mould is present, treat with Resene Moss & Mould Killer (see Data Sheet D80). Efflorescence on masonry **must be treated** (see Data Sheet D83).
- Remove accumulated windblown salt by washing with Resene Paint Prep and Housewash (see Data Sheet D812).
- Wherever oil and grease are present ensure the surface to be coated is thoroughly cleaned using Resene Paint Prep and Housewash. Flush clean with water.
- Waterblasting is the best surface preparation prior to coating of weathered cementitious surfaces.
- For heavy contamination scrub down with Resene Emulsifiable Solvent Cleaner (see Data Sheet D804) then rinse clean with water.
- All loose powdery material must be removed. If waterblasting is not possible thoroughly wire brush.
- **All sanding dusts may be harmful and appropriate protection must be worn. In particular dusts from old lead or chromate based paints or old building materials containing asbestos may be injurious to health if inhaled or ingested. Seek expert advice if the presence of these materials is suspected.**
- Fill cracks up to 2mm in cementitious surfaces with Resene Brushable Crack Filler. Fill cracks larger than 2mm in cementitious surfaces with a suitable elastomeric paintable sealant after priming with Resene Sureseal (see Data Sheet D42).
- Fill cracks and holes in interior walls before sealing.
- This product may be used to coat a wide variety of surfaces. If the surface you propose to coat is unsound or not referred try a small area first or contact your local Resene ColorShop or Reseller.

Priming

- All surfaces which are in poor condition or affected by efflorescence or which are friable, powdery or chalky must be primed with Resene Sureseal.
- Sealants - special coating requirements of construction sealants and fillers should be followed.
- Sound cementitious surfaces do not normally require a primer.
- Ensure cementitious surfaces are fully cured, or treated with Resene Limelock (see Data Sheet D809), before coating.
- Paperfaced plasterboard must be prepared to an appropriate level of finish. Either Resene Broadwall Surface Prep & Seal (see Data Sheet D807), Resene Broadwall 3 in 1 (see Data Sheet D810) or Resene Sureseal (see Data Sheet D42) followed by lining paper is recommended in critical lighting areas.
- Hardboard must be sealed (e.g. Resene Sureseal - see Data Sheet D42 or Resene Waterborne Smooth Surface Sealer - see Data Sheet D47a) to promote flow of the topcoats. Use Resene Sureseal if the surface is water stained.

- Some 'soft' paperfaced plasterboard preparatory products and undercured gypsum based stoppings may not be suitable basecoats for painting under stressed conditions. Reinforcement with a saturation coat of a fully penetrating primer (such as Resene Sureseal or Resene Waterborne Smooth Surface Sealer) may be required. Use Resene Sureseal if the surface is water stained.

Application

- Prepare and prime surface as per schedule above.
- The finished texture will vary according to application rate and spray technique.
- The complete coating system comprises a basecoat of Resitex Anchor Coat followed by Resitex Standard, Medium, Coarse or Plastercote depending on desired texture.

Basecoat:

- **Resitex Anchor Coat** is to be used as the basecoat for all finishes. Apply one coat of Resitex Anchor Coat at 6.5 square metres per litre with a PAL Hi-Solid roller sleeve.

Topcoats:

- **Coarse:** Spray: Apply one coat of Resitex Coarse at 2.5-3 square metres per litre with a hopper gun 8mm tip using a circular motion.
- **Medium:** Spray: Apply one coat of Resitex Medium at 2.5-3 square metres per litre with a hopper gun 8mm tip using a circular motion.
- **Standard:** Spray: Apply one coat of Resitex Standard at 3-3.5 square metres per litre with a hopper gun 5mm tip in smooth even passes. PAL Hi-Solid roller sleeve: Apply two coats of Resitex Standard at 6-7 square metres per litre laying off to avoid join marks.
- **Plastercote:** Spray apply Resitex Plastercote at 2-3 square metres per litre with a hopper gun 8mm tip using a circular motion. Strike or swirl textures can be achieved by plastic floating of the wet spray applied Plastercote with a vertical or circular motion respectively. Touch ups should be avoided, as differences in appearances may be apparent.
- Additional, attractively different texturing effects can be created using greater amounts of Resitex. Application in two coats is always recommended for uniformity
- Full toughness requires at least 48 hours to develop in average drying conditions.



Resitex Coarse SDS



Resitex TDS

Resene
the paint the professionals use

In Australia: Resene Paints (Aust) Limited
7 Production Ave, PO Box 924, Beenleigh, Qld 4207
Phone 1800 738 383 Fax 1800 064 960
Email advice@resene.com.au or visit www.resene.com.au

In New Zealand: Resene Paints Limited
Vogel Street, PO Box 38242, Wellington Mail Centre, Lower Hutt 5045
Phone (04) 577 0500 Fax (04) 577 0600
Email advice@resene.co.nz or visit www.resene.co.nz

Manufactured under a quality system certified as complying with ISO9001 by Telarc SAI, an accredited certification body. This product complies with all the requirements of an APAS Paint Specification. Refer to the APAS Specification list on the Resene website for full details. Printed on environmentally responsible paper, which complies with the requirements of environmental management systems EMAS and ISO14001, using vegetable-based inks.

Quick check

Use on: Exterior and interior cementitious surfaces, solid plaster, GRC and suitably primed wallboards. Resene Resitex Plastercote may also be used on galvanised steel and Zinalume. **Gloss level:** Satin.

Coverage: **Coarse:** 2.5-3 square metres per litre per coat (spray application). **Medium:** 2.5-3 square metres per litre per coat (spray application). **Standard:** 3-3.5 square metres per litre per coat (spray application). **Plastercote:** 2-3 square metres per litre per coat (spray application only).

Application rates vary depending upon choice of texture and application method. **Dry time (minimum):** 2 hours (depending on film thickness). Do not apply at temperatures below 10°C or when temperatures are liable to drop below this during the drying period. Drying is slowed by low temperatures and high humidity. Do not apply under damp conditions.

Recoat time (minimum): 2 hours. Allow 8 hours if overcoating with Resene Multishield+ (see Data Sheet D54a). **Primer required:** Dependent upon surface.

Usual number of coats: Sprayed, one coat; rolled, two coats.

Application method: Resene Resitex: Spray and/or PAL Hi-Solid roller. Resene Resitex Plastercote: Spray application only.

Clean up: Water. **Colour range:** Selected Resene Total Colour System including BS5252, Multi-finish, Whites & Neutrals and The Range.

Before use: Stir well with a wide flat stirrer.

Enjoy the Resene Promise of quality on premium paints. See your Resene ColorShop or the Resene website for a copy. In every case it is recommended that the appropriate Data Sheet and Safety Data Sheet are consulted prior to application.

Please ensure that use of this product is compatible with the substrate and surface preparation method and that the colour in this container is the same as selected. When using multiple packs of this product on the same project please mix them together before use. Resene does not accept any responsibility for the application of incorrect product to substrate or the application of incorrect colours. For further painting advice and information, call 1800 738 383 (AUST), 0800 737 363 (NZ) or visit the Resene website.



9 418022 005810

**COARSE
WHITE**