

Resene product labels are updated from time to time. This label is provided as a guide for this product and may differ from the label on the container you purchase.
Please discuss your project with your local Resene ColorShop team or reseller to ensure you have the right products to give you the best quality finish for your specific project.

SAFETY PRECAUTIONS

Read label before use. Keep out of reach of children. Causes serious eye irritation. Causes mild skin irritation. May cause an allergic skin reaction. Suspected of damaging fertility or the unborn child.

PRECAUTIONS

AVOID BREATHING DUST, MISTS, VAPOURS OR SPRAYS. DO NOT EAT, DRINK OR SMOKE WHEN USING THIS PRODUCT.

Store in original or correctly labelled container, tightly closed, in a well-ventilated area indoors, away from foodstuffs, at an ambient temperature and avoid freezing conditions. Store locked up. Wear protective gloves and clothing, eye and face protection. Ground and bond container and receiving equipment. Use explosion-proof electrical, ventilating, lighting and intrinsically safe equipment. Use non-sparking tools. Take action to prevent static discharges. Contaminated work clothing should not be allowed out of the workplace. Obtain special instructions before use.

FIRST AID

IF SWALLOWED: Call a POISON CENTRE, doctor or first aider if you feel unwell.

IF ON SKIN (or hair): Wash with plenty of soap and water. If skin irritation or rash occurs get medical advice or attention. Take off contaminated clothing and wash before reuse.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists get medical advice or attention.

IF INHALED: If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms call a POISON CENTRE, doctor or first aider.

When seeking medical advice take this container with you.

Further information can be obtained from

AUST: POISONS INFORMATION CENTRE 131 126

or call Resene 1800 738 383.

NZ: NATIONAL POISONS CENTRE 0800 POISON (764 766)

or call Resene 0800 737 363.

For use as a surface preparation coating.

For full technical instructions see Data Sheet D406.

SPILLS: Use appropriate protective clothing. Absorb with sand or earth. Collect and seal in properly labelled drums. Do not allow to enter drains or to run off into waterways. Refer to local waste management authority.

CLEANING PAINT EQUIPMENT: Brush/roll out as much paint as possible on to newspaper before washing out brushes/rollers with Resene Brush Cleaner. Do not allow to enter any drains. Refer to your local Council for disposal.

FIRE: Use foam, carbon dioxide or dry chemical powder.

WARNING

KEEP OUT OF REACH OF CHILDREN

Resene**Vinyl Wallpaper
Sealer**

interior



Resene Vinyl Wallpaper Sealer is formulated to seal in the plasticiser found in vinyl wallpapers. Vinyl wallpaper coated directly with standard paint finishes can become sticky as the plasticiser in the wallpaper migrates through the paint finish affecting its cure.

Preparation

• Ensure surfaces to be painted are in a sound condition, dry, free from dirt, dust and loose material. Cleaning methods should be with soft cloths as abrasives will damage the paper surface. Allow to dry.

• Thoroughly clean down the surface to remove all loosely adhered material. Treat areas of moss or mould infestation with Resene Moss & Mould Killer (see Data Sheet D80), correctly diluted with water. Leave for up to 48 hours to achieve full kill. For heavy infestations further applications may be needed. Wash thoroughly with clean water to remove residues.

• This product may be used to seal a wide variety of wallpapers. If the surface you propose to seal is unsound or not referred to, try a small test area first or contact your local Resene ColorShop or reseller for advice.

Application

• Resene Vinyl Wallpaper Sealer is very fast drying so you need to work quickly.

• Apply one full coat to seal the wallpaper. Allow to dry for two hours before applying the topcoat system.

• If a very smooth level 5 finish is desired, apply Resene Vinyl Wallpaper Sealer. Allow to dry then skim coat the surface using Resene Broadwall Surface Prep & Seal (see Data Sheet D807) or Resene Broadwall 3 in 1 (see Data Sheet D810).

• Also see Data Sheet D84 and Specification Sheet 16i for full instructions on coating wallpaper.

• Maintain good ventilation throughout the drying and curing period to ensure the paint is properly cured. Poor ventilation may inhibit curing and performance.

Be PaintWise

For tips on responsible disposal of paint, cleaning equipment

and minimising the impact of your decorating on the environment see the Resene website. Do not discharge any paint into the environment. Resene PaintWise (NZ) or paintback.com.au (Australia) accepts residual unwanted paint and packaging. Or contact your Local Authority for disposal information.



UN NO. 1263 – PAINT RELATED MATERIAL



Vinyl Wallpaper Sealer SDS

Resene

the paint the professionals use

In Australia: Resene Paints (Aust) Limited
7 Production Ave, PO Box 924, Beenleigh, Qld 4207
Ph 1800 738 383 Visit www.resene.com.au

In New Zealand: Resene Paints Limited
Vogel St, PO Box 38242, Wgtn Mail Centre, Lower Hutt 5045
Ph (04) 577 0500 Visit www.resene.co.nz

Manufactured under a quality system certified as complying with ISO9001 by Telarc SA, an accredited certification body. Printed on environmentally responsible paper, which complies with the requirements of environmental management systems EMAS and ISO14001, using vegetable-based inks.

Quick check

Use on: Vinyl wallpaper. Specifically designed to seal in the plasticiser associated with vinyl wallpapers.

Coverage: 16 square metres per litre per coat.

Dry time (minimum): Touch dry 40 minutes. Drying is slowed by low temperatures and high humidity. Do not apply under damp conditions.

Recoat time (minimum): 2 hours.

Usual number of coats: One.

Application method: Brush, roller or spray. Resene Vinyl Wallpaper Sealer is very fast drying so you need to work quickly.

Thinning: Do not thin.

Clean up: Resene Brush Cleaner.

Overcoating: May be overcoated with standard acrylic or enamel systems

Before use: Stir well with a wide flat stirrer.

Enjoy the Resene Promise of quality on premium paints. See your Resene ColorShop or the Resene website for a copy.

In every case it is recommended that the appropriate Data Sheet and Safety Data Sheet are consulted prior to application.

FLAMMABLE LIQUID AND VAPOUR

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

Please ensure that use of this product is compatible with the substrate and surface preparation method and that the colour in this container is the same as selected. Resene does not accept any responsibility for the application of incorrect product to substrate or the application of incorrect colours. Resene products are designed to be used as a system for optimal results. Substitution may cause substandard results or system failure. For further painting advice and information, call 1800 738 383 (AUST), 0800 RESENE (NZ) or visit the Resene website.

