

Resene product labels are updated from time to time. This label is provided as a guide for this product and may differ from the label on the container you purchase. Please discuss your project with your local Resene ColorShop team or reseller to ensure you have the right products to give you the best quality finish for your specific project.

XC-700

**clear high build
concrete and masonry finish**
waterborne exterior/interior



KEEP OUT OF REACH OF CHILDREN



CLEAR

net contents 10 litres

tinter included

This is a controlled distribution product.

LL2870010B 5/15

WARNING

Read label before use. Keep out reach of children. This material is quite bland; with vapour, occasional skin contact and even minor ingestion having negligible hazard. Repeated skin contact may, and any eye contact will, cause irritation.

PRECAUTIONS

USE WITH ADEQUATE VENTILATION. DO NOT EAT, DRINK OR SMOKE WHILE USING.

Store in original or correctly labelled container, tightly closed, in a well ventilated area indoors, away from foodstuffs, either between 15°C-20°C or at a cool, constant temperature. Dispose of empty container safely. Consult Resene checklist on environmentally acceptable methods of cleaning equipment and disposing of unwanted paint. Do not contaminate any water supply. Avoid release to the environment.

FIRST AID

IF SWALLOWED: Rinse mouth. Call a POISON CENTRE or doctor/physician if you feel unwell.

IF ON SKIN (or hair): Remove/take off all contaminated clothing and wash before reuse. Rinse skin with plenty of soap and water/shower. If skin irritation or rash occurs: Get medical advice/attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing. If eye irritation persists: Get medical attention/advice. Further information can be obtained from AUST: POISONS INFORMATION CENTRE 131 126 or call Resene 1800 738 383.

NZ: NATIONAL POISONS CENTRE 0800 POISON (764 766) or call Resene 0800 737 363.

For use as a decorative/protective coating.

For full technical instructions see Data Sheet D54a.

SPILLS: Wear appropriate protective clothing. Absorb with sand or earth. Collect and seal in properly labelled drums. Do not allow to enter drains or to run off into waterways. Refer to local waste management authority.

CLEANING PAINT EQUIPMENT: Brush/roll out as much paint as possible onto newspaper before washing brushes and rollers. Dispose of wash-up water onto grassy/unsealed area or into inside sink/basin, NOT into outside stormwater drain where it may harm fish in local waterways.

Resene XC-700 is a clear high build finish designed to seal concrete and masonry walls for a lightly textured 'natural look' finish.

Preparation

- Ensure surfaces to be painted are in sound condition, dry, free from dirt, dust, loose material and salt. If moss or mould is present, treat with Resene Moss & Mould Killer (see Data Sheet D80).

- Remove accumulated windblown salt by prolonged washing with clean water.

- Waterblasting is the best surface preparation prior to coating of weathered cementitious surfaces. Ensure the wall is completely dry before coating.

- If mould is present, treat with Resene Moss & Mould Killer.

- Efflorescence on masonry must be treated (see Data Sheet D83).

- Wherever oil and grease are present ensure the surface to be coated is thoroughly cleaned using Resene Paint Prep and Housewash (see Data Sheet D812). Flush clean with water.

- Saturate the surface with Resene Solventborne Aquapel (see Data Sheet D65S) in accordance with the product data sheet.

- **All sanding dusts may be harmful and appropriate protection must be worn. In particular dusts from old lead or chromate based paints or old asbestos containing building materials may be injurious to health if inhaled or ingested. Seek expert advice if the presence of these materials is suspected.**

- This product may be used to coat a wide variety of surfaces. If the surface you propose to coat is unsound or not referred to, try a small test area first or contact your local Resene ColorShop or Reseller for advice.

Application

- Do not shake contents, rather stir well with a wide flat stirrer. To avoid foaming of material, do not shake and do not brush excessively.

- Do not apply in direct sunlight.

- Apply Resene XC-700 using a roller (Resene No.2 sleeve) at spreading rates of 1st coat 3.6 sqm/L, 2nd coat 4.6 sqm/L and 3rd coat 4.6 sqm/L. Total DFT 363 microns.

- Not recommended for exterior tile or decorative aggregate flooring where ponding occurs.

Be PaintWise

For tips on minimising the impact of your decorating on the environment see the Resene website.



XC-700 SDS

Resene

the paint the professionals use



XC-700 TDS

In Australia: Resene Paints (Aust) Limited
7 Production Ave, PO Box 924, Beenleigh, QLD 4207
Phone 1800 738 383 Fax 1800 064 960
Email advice@resene.com.au or visit www.resene.com.au

In New Zealand: Resene Paints Limited
Vogel Street, PO Box 38242, Wellington Mail Centre, Lower Hutt 5045
Phone (04) 577 0500 Fax (04) 577 0600
Email advice@resene.co.nz or visit www.resene.co.nz

Manufactured under a quality system certified as complying with ISO9001 by Telarc SA, an accredited certification body. Printed on environmentally responsible paper, which complies with the requirements of environmental management systems EMAS and ISO14001, using vegetable-based inks.

Quick check

Use on: Concrete masonry and honed concrete walls.

Gloss level: Flat.

Typical coverage: 1st coat 3.6 sqm/L, 2nd coat 4.6 sqm/L and 3rd coat 4.6 sqm/L. Total DFT 363 microns.

Coverage will vary dependent upon surface porosity and profile. Weathertightness requires the full system to be applied to achieve the required system dry film thickness.

Dry time (minimum): 2 hours, depending on film thickness. Do not apply at temperatures below 10°C or when temperatures are liable to drop below this during the drying period.

Recoat time (minimum): 4 hours, depending on film thickness. Drying is slowed by low temperatures and high humidity. Do not apply under damp conditions.

Primer required: Yes, concrete block must be treated with Resene Solventborne Aquapel.

Usual number of coats: 3.

Application method: Roller (Resene No.2 roller sleeve).

Thinning and clean up: Do not thin. Clean up with water.

Colour range: Clear.

Before use: Stir well with a wide flat stirrer.

Enjoy the Resene Promise of quality on premium paints. See your Resene ColorShop or the Resene website for a copy. In every case it is recommended that the appropriate Data Sheet and Safety Data Sheet are consulted prior to application.

Please ensure that use of this product is compatible with the substrate and surface preparation method and that the colour in this container is the same as selected. When using multiple packs of this product on the same project please mix them together before use. Resene does not accept any responsibility for the application of incorrect product to substrate or the application of incorrect colours. For further painting advice and information, call 1800 738 383 (AUST), 0800 737 363 (NZ) or visit the Resene website.